

Parameters estimation of active contour models for the problem of automatic cellular filaments tracking

Dmytro Kotsur¹, Reinhard Windoffer², Rudolf E. Leube²,
Sergei Pereverzyev³, Julian Mattes⁴

¹ Software Competence Center Hagenberg GmbH, Hagenberg, Austria

² Institute of Molecular and Cellular Anatomy, RWTH Aachen University, Aachen, Germany

³ Radon Institute for Computational and Applied Mathematics, Linz, Austria

⁴ MATTES Medical Imaging GmbH, Hagenberg, Austria

[dmytro.kotsur@scch.at]

Active contour models or snakes [1] are widely used and have large application area in computer vision, image analysis and especially in the analysis of biomedical and microscopic images. In this work we apply gradient vector flow-based [2] active contour models for segmentation and tracking of cellular intermediate filaments. As a part of the cells cytoskeleton, these filaments have notable diversity between different cell-types and play a crucial role in the mechanical behaviour and properties of living cells [3].

The best fitting position of the active contour (snake) to an observed filament on the selected image can be obtained by minimizing a parametrized energy functional of the snake, which incorporates elastic properties of the contour as well as the image data term. The latter can be replaced, according to [2], by a vector field called gradient vector flow, which provides better convergence [2] of the method in case of concavities compared to [1].

In this work we focus on the problem of automatic estimation of the models free parameters [4] based on an image data driven approach. The resulting method is incorporated into our image analysis framework comprising automatic filaments detection and tracking.

Acknowledgements

This project has also received funding from the European Union's Horizon 2020 research and innovation program under the Marie Skłodowska-Curie grant agreement No. 642866.

References

- [1] Kass, M., Witkin, A., & Terzopoulos, D. (2002). Snakes: Active contour models. *International Journal of Computer Vision*, 1(4), 321-331.
- [2] Xu, C., & Prince, J. L. (1997). Gradient vector flow: a new external force for snakes. In *Proceedings of IEEE Computer Society Conference on Computer Vision and Pattern Recognition*. IEEE Comput. Soc.
- [3] Leube, R.E., Moch, M., and Windoffer, R. (2017). Intracellular Motility of Intermediate Filaments. *Cold Spring Harb Perspect Biol* June 2017.
- [4] Chen, J., Pereverzyev Jr, S., & Xu, Y. (2015). Aggregation of regularized solutions from multiple observation models. *Inverse Problems*, 31(7).